



- NOTES:
1. All dimensions are in millimeters.
 2. Remove all burrs and sharp edges, all holes must be free of burrs or wastes
 3. All dimensions include the material treatment thickness.
 - 4.
 5. Unless otherwise specified, cutting tolerances according ISO 2768-m.
 6. Holes diameter tolerance $\pm 0,5$ mm.
 7. Hot galvanizing according to ISO 1461 and ASTM 123
 8. Dimentions according to supplier requirements

E-110_C_AxBxCxD_L										see"D"		PILAR LATERAL C/C LATERAL PILE										S355JR			
PLAN										THICKNESS		DESCRIPTION										PESO/WEIGHT		MATERIAL	
Drawing												Rev./ Rev.		Escala/Scale:		Hoja/Sheet									
E-110_C_AxBxCxD_L														A3											
Diferencias para cotas sin tolerancias (mm) Difference in sidecuts without tolerance (mm)														FECHA/DATE:		NOMBRE/NAME:		MECANIZADOS SOLARES S.L. Plaza de la Encina 10-11, Núcleo 5, 3ª Planta 28760 Tres Cantos (Madrid) www.mecasolar.com							
de		0	6	30	100	300	>1000		Dibujado/Drawn		24/04/2024														
a		6	30	100	300	1000			Revisado/Checked		24/04/2024														
±		0,1	0,2	0,3	0,5	0,8	1		Aprovado/Approved		24/04/2024														
Plano propiedad de MECASOLAR S.L. esta prohibido reproducir o comunicar sin autorización Drawing property of MECASOLAR S.L. is prohibited reproduce or communicate without authorization																		HOJA 1 DE 1							